

NEC MultiSync® E223W

Order Code: 60003334 (BK), 60003335 (WH)

NEC LCD 22" Commercial Display

NEC MultiSync E223W features an extremely thin LED backlight panel which results in an ultra-modern and slim design in combination with a perfect feature set for the standard corporate office. The display offers 110 mm height adjustment and a broad connectivity with three inputs DisplayPort, DVI-D and D-Sub.

Ideal for the corporate that demand style and future proof technology.

DELIVERING GENUINE BENEFITS

Image display - 22inch 16:10 TN with LED backlight.

Ergonomic Office - full height adjustability (110 mm), swivel, tilt and pivot functionality ensures perfect individual ergonomic set-up.

Vesa Mount (100 mm) - allows to install the monitor via various mounting solutions.

Free Download of Multi-Display Management Software - with NaViSet Administrator 2 you can manage all your connected display devices from a centralized location.



NaViSet
Administrator 2

OUTSTANDING PERFORMANCE

- **Ultra-modern and slim design.** The product design is discrete and puts priority on the screen image and function.
- **Excellent ergonomics.** The ergonomic stand with 110 mm height adjustability allows greatest set-up flexibility.
- **Low energy consumption** with LED backlight and unique Carbon Savings Meter.



SPECIAL CHARACTERISTICS

Carbon Footprint Meter, Carbon Savings Meter, EcoModes, ErgoDesign®: Height adjustable stand (110 mm) with 90° Pivot features, NaViSet Administrator 2, sRGB Support, Touch Sensor Keys, WindowsVistaCertifiedLogo



Energy Efficiency Carbon Footprint Meter / Carbon Savings Meter; ECOMode; Intelligent Power Management; LED backlight technology

Ecological Materials Downloadable manuals

Ecological Standards TCO 5.2

Technical Specification NEC MultiSync® E223W

DISPLAY	
Panel Technology	W-LED TN TFT
Screen Size [inch/cm]	22 / 55.87
Screen Aspect Ratio	16:10
Pixel Pitch [mm]	0.282
Brightness (typ.) [cd/m²]	250
Contrast Ratio (typ.)	1000:1 (25000:1 dynamic contrast ratio)
Viewing Angle [°]	170 horizontal / 160 vertical (typ. at contrast ratio 10:1); 178 horizontal / 178 vertical (typ. at contrast ratio 5:1)
Response Time (typ.) [ms]	5
Colours [Mio.]	16.7
SYNCHRONISATION RATE	
Horizontal Frequency [kHz]	31.5 - 82.3
Vertical Frequency [Hz]	56 - 75
RESOLUTION	
Optimum Resolution	1680 x 1050 at 60 Hz
Supported	1680 x 1050; 1600 x 1200; 1440 x 900; 1400 x 1050; 1366 x 768; 1360 x 768; 1280 x 1024; 1280 x 960; 1280 x 768; 1280 x 720; 1024 x 768; 800 x 600; 640 x 480
CONNECTIVITY	
Digital	1 x DVI-D (with HDCP); 1 x DisplayPort
Analog	1 x mini D-sub 15 pin
ELECTRICAL	
Power Consumption on Mode [W]	17 (typ.); 12 (Eco Mode); 24 (max.)
Power Savings Mode [W]	0.35
Power Supply	100-120 V/220-240 V; 1 A/0.5 A; integrated power supply
ENVIRONMENTAL CONDITIONS	
Operating Temperature [°C]	+5 to +35
Operating Humidity [%]	20 to 80
ERGONOMICS	
Height adjustable stand [mm]	110
Screen Tilt / Swivel [°]	-5 to +20; -45 to +45
Screen Rotate [°]	0 to 90 (landscape to portrait mode)
MECHANICAL	
Bezel Width [mm]	13.9 (left and right); 15.8 (top and bottom)
Dimensions (W x H x D) [mm]	503.5 x 383.3 x 213.9
Weight [kg]	5.6
VESA Mounting [mm]	100 x 100
ADDITIONAL FEATURES	
Colour Versions	White Front Bezel, White Back Cabinet, Black Front Bezel, Black Back Cabinet
Cable Management	yes
Kensington security slot	yes
Plug and Play	VESA DDC/Ci; DDC2B/2Bi
Adjust Functions	Auto Adjust; Brightness; Colour Temperature Control; Contrast; DV Mode; EcoMode; Fine Adjust (analog); Intelligent Power Management; Language Select; LED Brightness; Monitor Information; NTAA (Non-Touch-Auto-Adjustment); On-Screen-Display (OSD) lock-out; Power-Off Timer; sRGB
Shipping Content	Monitor; Power Cable; CD-ROM; Sales Office List; User Manual Signal Cable: VGA - VGA; DVI-D - DVI-D
Safety and Ergonomics	EPEAT Silver™; EPEAT™ Gold (black version); CE; ErP; TCO 6.0; TÜV Ergonomics; TÜV GS; GEEA/Energy Label; Energy Star 5.0; FCC Class B; PCT/Gost; UL/C-UL or CSA; ISO 9241-307 (pixel failure class I); MPR II/ MPR III; RoHS
Warranty	3 years warranty incl. backlight